

# MIAXIS®

# MX730

## FINGERPRINT TIME ATTENDANCE



MX730 adopts world leading Justouch fingerprint algorithm with super fast fingerprint verification speed. It is a portable standalone device with capacity of 3000 fingerprints and 130,000 attendance records. It supports records output without connecting to PC, and real-time uploading records. It has communications of RS232/RS485,TCP/IP,USB and supports WEB online tracking for multi-devices. Fingerprint verification with high dependability and accuracy, it is a good option for enterprise/ office/factory/bank/restaurant etc.



MIAXIS BIOMETRICS CO.,LTD

Add:12F, Technology Bldg., East Software Park,  
No.90 Wensan Rd, Hangzhou, 310012, P.R.China  
Tel:+86-571-81951588 Fax:+86-571-81951600  
Http://www.miaxis.com E-mail:business@miaxis.com

## Product Features

- ◆ World-Known Brand Maxis, large LCD.
- ◆ SamSung 32 bit ARM920T, strong image processing, high performance and reliability.
- ◆ Maxis SM621 optical sensor, scratch-resistant, durable, blue background light.
- ◆ World leading Justouch fingerprint algorithm, self-adjust fingerprint image reading, well accept all kinds of fingerprints.
- ◆ Support ID/EM card with working frequency 125KHZ, thickness of 1.88mm, 1.05mm and 0.88mm.
- ◆ Support user name display, optional ID Number.
- ◆ Support user-defined Logo.
- ◆ fingerprint capacity: 3,000, record capacity: 130,000.
- ◆ Support RS232/RS485, TCP/IP, USB communication.
- ◆ Support real-time records collection.
- ◆ Wall mounted, unique self-lock design.
- ◆ Easy-to-use software, suitable for all kinds of complicated time attendance management.
- ◆ Export office Excel file for management.

## Specifications

Item	Description
Sensor	SM621 optical fingerprint sensor
Scan area	17mm × 21.5mm
Resolution	500DPI
Identification method	Fingerprint 1:1, 1:N, password, ID card+fingerprint
FRR	<0.01%
FAR	<0.0001%
Identification time	<1s, 3,000 fingerprints, 1:N
Register method	Fingerprint, password
Fingerprint capacity	3,000 fingerprints
User capacity	≤3,000 persons
Record capacity	130,000
Communication	RS232/RS485, TCP/IP, USB
LCD	128 × 64 LCD
Language	English, Chinese ( can be customized )
User interface	16 keypads, voice prompts
Work current	≤450mA
Standby current	≤120mA
ESD	>15000V
Power supply	DC 5V@1A
Working temperature	-10℃ ~ +60℃
Working humidity	+20% ~ +90% ( no dew )
Size	195mm × 150mm × 34mm
Color	Silver, black, golden, blue ( can be customized )

## Diagram

